

(2) In a case where the length of the flying machine is 150 feet or upwards, it shall display, in addition to any other light required by this rule, a white light at or near its stern at a lower height than the forward light mentioned in clause (1), and visible all round the horizon at a distance of at least one mile.

(3) In a case where the maximum span of the flying machine is 150 feet or upwards, it shall display, in addition to any other light required by this rule, a white light on each side placed in such a manner as to demarcate the maximum lateral dimension of the flying machine and visible, so far as practicable, all round the horizon at a distance of at least one mile.

Gliders.

95. In all cases in which flying machines are required by these rules to display lights, a glider shall display a red light visible, so far as practicable, in all directions.

Balloons and Kites.

96. **Free balloons.**—A free balloon shall display a red light placed not less than 15 or more than 30 feet below the basket and visible so far as practicable, in all directions at a distance of at least two miles.

97. **Captive balloons and kites.**—In the case of a captive balloon or kite, lights shall be displayed in accordance with the following provisions, namely:—

(1) when flown at an altitude exceeding 180 feet above the ground, or at any altitude if it is less than three miles from an aerodrome or from a recognized air-route the balloon or kite shall display a white light placed 12 feet vertically above a red light, these lights being visible so far as practicable in all directions at a distance of at least two miles, the upper white light being placed not less than 15 or more than 30 feet below the basket, or, if there is no basket, below the lowest part of the balloon or kite;

(2) in addition, from the mooring cable of the balloon or kite there shall be displayed at intervals of 1,000 feet measured from the said group of two lights, similar groups of two lights, one white and one red, and if the lowest group of lights is obscured by clouds, an additional group shall be displayed below the cloud base;

(3) in addition, the position of the object to which the balloon or kite is moored on the ground shall be marked by a group of three flashing lights, arranged on a horizontal plane at the apexes of a triangle approximately equilateral and measuring at least 75 feet on each side; the side of this triangle, perpendicular to the horizontal projection of the cable, shall be delimited by two red lights, the third light shall be a green light placed opposite the direction of the cable.

98. **Day markings for captive balloons.**—By day, the mooring cable of a captive balloon shall have attached to it at intervals of not more than 600 feet measured from the basket (or, if there is no