6505-527-6885 (P. D. No. 4)

Packing. Packing shall be in accordance with 5.4 with the following exceptions:

5.4.3 Level B. Delete 200 lbs. bursting strength wherever referenced and substitute "Bursting strength of carton shall be in accordance with special requirements in table I of PPP-B-636."

5.4.4 Level A. Delete entirely and substitute:

"5.4.4 Level A. Items shall be packed for the degree of protection specified for Level B, and shall be further protected by being overpacked in an exterior container designed for type 1 load and constructed in accordance with PPP-B-585, style 3 for class 3 use; PPP-B-601, table III, using type I, class 1 plywood; PPP-B-621, table III; or PPP-B-636, type CF, class weather resistant. Bursting strength of fiberboard box shall be in accordance with special requirements of table II of PPP-B-636. Grade W5 shall not be permitted for exterior container. Closure of wood boxes shall be in accordance with appendix of applicable box specification. Closure of each fiberboard box shall be as specified in the appendix, and waterproofing shall conform with paragraph 30.4 of PPP-B-636."

5.4.4.1 Waterproof barrier. Delete entirely and substitute:

"5.4.4.1 Case liner. Each Level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes."

5.5 Marking. Delete and substitute:

"5.5 Marking.

- "5.5.1 Intermediate package. Each intermediate package shall be marked in accordance with Military Standard MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Lot (control) number, contract or purchase order number, and name of contractor shall be shown. Type I Shelf-Life markings as specified in paragraph 5.2.2.1 (a) of MIL-STD-129 shall be shown, except that date of manufacture shall not be shown.
- "5.5.2 Exterior containers. Exterior container shall be marked in accordance with Military Standard MIL-STD-129. Lot (control) number shall be shown. Type I Shelf-Life markings as specified in MIL-STD-129 shall be shown, except that date of manufacture shall not be shown.