

10384 COMPETITIVE PROBLEMS IN THE DRUG INDUSTRY

6505-299-9678 (P. D. No. 6)

Packing.

Level B.

Exterior container. Exterior container shall be a box of appropriate size constructed in accordance with PPP-B-636, type CF, class domestic. Bursting strength of box shall be in accordance with special requirements of table II of PPP-B-636. Closure shall conform to method II as specified in the appendix of the box specification.

Level A. Items shall be packed for the degree of protection specified for Level B, and shall be further protected by being overpacked in an exterior container designed for a type 1 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Bursting strength of fiberboard box shall be in accordance with special requirements of table I in PPP-B-636. Closure and strapping of boxes shall be as specified in the appendix of the applicable box specification.

Case liner. Each Level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes. Each fiberboard box shall be waterproofed in accordance with paragraph 30.4 of PPP-B-636.

Marking.

Unit package. Each unit package shall bear the same information as required for the immediate containers.

Exterior container. Exterior container shall be marked in accordance with MIL-STD-129. Lot (control) number shall be shown. Date of manufacture shall be shown in lieu of date packed. Marking shall include the legend:

"DO NOT PERMIT TO FREEZE."