

(4) No person shall cause or permit any materials to be handled, transported, or stored in a manner which allows or may allow particulate matter to become airborne. No person shall cause or permit a building or its appurtenances or a road to be constructed, altered, repaired or demolished without taking reasonable precautions to prevent particulate matter from becoming airborne.

(5) The maximum allowable emission of particulate matter from any source, except fuel-burning equipment and incinerators, shall be determined in accordance with the table set out below. Where the process weight per hour falls between two values in the table, the maximum weight discharged per hour shall be determined by linear interpolation. The table is as follows:

Process weight per hour (pounds)	Maximum weight discharge per hour (pounds)	Process weight per hour (pounds)	Maximum weight discharge per hour (pounds)
50	0.24	3300	5.36
100	0.46	3400	5.44
150	0.66	3500	5.52
200	0.85	3600	5.61
250	1.03	3700	5.69
300	1.20	3800	5.77
350	1.35	3900	5.85
400	1.50	4000	5.93
450	1.63	4100	6.01
500	1.77	4200	6.08
550	1.85	4300	6.15
600	2.01	4400	6.22
650	2.12	4500	6.30
700	2.24	4600	6.37
750	2.34	4700	6.45
800	2.43	4800	6.52
850	2.53	4900	6.60
900	2.62	5000	6.67
950	2.72	5500	7.03
1000	2.80	6000	7.37
1100	2.97	6500	7.71
1200	3.12	7000	8.05
1300	3.26	7500	8.39
1400	3.40	8000	8.71
1500	3.54	8500	9.03
1600	3.66	9000	9.36
1700	3.79	9500	9.67
1800	3.91	10000	10.00
1900	4.03	11000	10.63
2000	4.14	12000	11.28
2100	4.24	13000	11.89
2200	4.34	14000	12.50
2300	4.44	15000	13.13
2400	4.55	16000	13.74
2500	4.64	17000	14.36
2600	4.74	18000	14.97
2700	4.84	19000	15.58
2800	4.92	20000	16.19
2900	5.02	30000	22.22
3000	5.10	40000	28.30
3100	5.18	50000	34.30
3200	5.27	60000	40.00

When the process weight is in excess of sixty thousand pounds per hour, there shall not be discharged in any one hour from any source particulate matter in excess of 0.066 per centum of the process weight per hour.

(6) Stack emission tests for particulate matter shall be undertaken by generally recognized standards or methods of measurement. Methods found in the A.S.M.E. Test Code for Dust Separating Apparatus, PTC 21-1941, the A.S.M.E. Test Code for Determining Dust Concentrations in Gas Streams, PTC 27-1957, and the Los Angeles County Source Testing Manual shall be used, but these may be modified or adjusted by the Commissioner to suit specific sampling conditions or needs based upon good practice, judgment, and experience.