

will be firmly fastened to the seat and floor.

b. Seat cushions and back with springs broken or collapsed forming a depression will be repaired. Cushions and backs with two or three springs broken in scattered areas are acceptable if the broken ends of springs have not penetrated the seat and floor.

c. Vehicles with torn or frayed seat covers may have the covers removed if the original upholstery is still in a presentable condition. If covers are removed the seats should be vacuum cleaned to remove accumulations of dirt.

d. New floor mats will be installed in vehicles as required, or floor will be painted black, if mats are not available.

6. Serviceability Standards.

6.(A) Diesel Engines

1. Injectors, Fuel Pump.

Engines having loss of power, missing, or excessive smoking, will be given a tune up. Injectors will be removed, cleaned, repaired and/or calibrated when required. Fuel pumps will be serviceable.

2. Injector Rack.

Inspect injector rack for excessive wear. Adjust in accordance with applicable Technical Manual or Technical Order or Manufacturer's Specifications, when required.

3. Blower will be inspected for scored rotors, housing or end plates, when necessary. Oil seals having leaks will be replaced.

4. A. Gasoline starting motors. Change over system will be capable of starting the main engine.

B. During test engine runs smoothly and shows no sign of oil leaks or excessive oil consumption, engine will be acceptable. Normal operational oil seepage is acceptable.