

EXHIBIT 4

One example of the many specifications prepared by the military for Government use only and containing valuable consumer information relates to resilient floor coverings. Information thought to be of most value to consumers has been italicized.

DEPARTMENT OF THE NAVY

BUREAU OF YARDS AND DOCKS

Type Specification TS-F17, February 28, 1964, Superseding TS-RF1

Type specifications shall not be referenced but are to be used as manuscripts in preparing project specifications. Appropriate changes and additions as may be necessary and as required by the notes must be made. Numbers in parentheses—e.g., "(2)"—in right-hand margin refer to corresponding notes at end of specification.

Resilient Floor Coverings

1. *Scope.*—This section includes resilient floor coverings, complete. (N)

2. *Applicable documents.* (N)—The following specifications and standards of the issues listed in this paragraph (including the amendments, addenda, and errata designated), but referred to hereinafter by basic designation only, form a part of this specification to the extent required by the references thereto. (See paragraph entitled "Specifications and Standards" in sec. 1 for additional information.) (8)

2.1. *Federal specifications.*—(N)

L-F-450-----	Flooring, vinyl plastic.
L-T-345-----	Tile, floor, vinyl-asbestos.
O-P-106-----	Paste, linoleum.
P-W-155-----	Wax, floor, water-emulsion, slip resistant.
SS-A-128-----	Adhesive, asphalt, cutback type (for asphalt tile).
SS-A-138-----	Adhesive; asphalt, water emulsion type (for asphalt tile).
SS-A-701-----	Asphalt primer (for) roofing and waterproofing.
SS-T-306-----	Tile, floor, asphalt.
SS-T-301-----	Tile, floor, rubber.
LLL-L-351-----	Linoleum, battleship.
LLL-L-367-----	Linoleum, plain, jasper and marbled.

3. *Requirements.*—

3.1. *General.*—The provision of all _____ asphalt tile, _____ vinyl-asbestos tile, _____ homogeneous vinyl tile, _____ homogeneous vinyl roll, _____ rubber tile, _____ linoleum, _____ cove base _____, and all materials indicated, specified, or necessary for a complete and finished installation is included. Floor covering work shall not be started until the work of other trades, including painting, _____ but excluding movable partition work _____ is substantially completed. Spaces in which floor covering work is to be performed shall be maintained at not less than 70° F. at the floor level for at least 48 hours prior to starting the work, during the time work is performed, and for at least 48 hours after the work is completed. Adequate ventilation shall be provided to remove moisture and fumes from the area. Two current copies of the floor covering manufacturer's recommended standard installation procedure for each type of floor covering material shall be submitted for approval before the work is started.

3.2. *Materials* shall be delivered to the job in the manufacturers' original unopened containers, with the brands and names clearly marked thereon. (R) All materials shall be carefully handled and shall be stored in their original containers at not less than 70° F. for at least 24 hours before work is started. Containers shall not be opened until approved. Floor coverings shall be provided in colors as selected from manufacturer's standard colors. Borders, feature strips, and other accessories indicated or necessary shall be the standard products of the manufacturer of the floor covering, as approved. The color and pattern of tile shall be uniformly distributed throughout the thickness of the tile.